GRASEN DCFC 60kW - 150kW

DC Rapid The Power of Speed





Flexible Charging Port Options

Support CCS1, CCS2, CHAdeMO or GBT connector. Charging two vehicles simultaneously.



High-Speed Charging

Max output power 60kw~150kW, average charging time 30~60mins.



Easy Operating

White-labeled hardware and software, manage multiple charging stations via cloud-based CSMS.



Safety & Reliable

CE Certified quality, IP55 rated for outdoor application, with a standard 2-year warranty.

Benefits

- Max 125A/200A 1000V
- Durable and safe for both indoor and outdoor use
- 8" LCD touch screen with multi-language interface
- SAE Combo, CHAdeMO, GBT optional charging connector
- Network connection via WIFI, Ethernet, 4G
- OCPP 1.6J, OCPP 2.0
- Dynamic load management
- Software free-update

Application Area

- Commercial and public parking lot
- Fleet operators
- EV dealerships
- Service station



GRASEN DCFC 60kW - 150kW





Technical Specifications 60kW 90kW 120kW 150kW

Input	Input Voltage	400V±15% / 440V±15% / 480V±15%
	Input Voltage Type	TN-S
	Working Frequency	45~65Hz
	Power Factor	≥0.99
	Efficiency	≥94%
Output	Rated Voltage	CHAdeMO 500Vdc; CCS 1000Vdc; GBT 1000Vdc
	Max Output Current	CHAdeMO 125A; CCS 200A; GBT 250A
Interface	Display	8" LCD Touch Screen
	Emergency Stop Button	Yes
	Payment	Mobile APP / RFID / POS
Communication	Network Connection	4G(GSM or CDMA) / Ethernet / WIFI
	Communication Protocols	OCPP1.6J or OCPP2.0
Working Environment	Working Temperature	-30℃ ~ +50℃
	Storage Temperature	-40°C ~ +70°C
	Operating Humidity	≤95% Non-Condensing
	Protection	IP55
	Acoustic Noise	< 60dB
	Cooling Method	Forced Air-Cooling
Mechanical	Dimension(W x D x H)	1006mm*640mm*1890mm
	Weight	310 ~ 420kg
	Cable Length	5m or 7m
Regulation	Certificate	TUV CE / IEC61851-1 / IEC61851-23 / IEC61851-21-2
	Charging Interface	DIN70121 / DIN70122 / ISO15118

^{*}Please note that this is preliminary data—the final product and data are subject to change.